



OLEOFLOOR® TRADITION

DURABLE OIL FOR PARQUET FLOORING AND WOODEN STAIRCASES

Description	OLÉOFLOOR® TRADITION is a highly nourishing and durable oil that is specially designed for the impregnation of parquet flooring and wooden staircases subject to heavy use.
Basic uses	Parquet flooring or wooden staircases. Particularly floors subject to very heavy use.
Technical data	<p>Colour: Slightly amber Vehicle type: Alkyd Solvent type: White-Spirit Specific gravity (at 20°C): 0.91 ± 0.02 Viscosity at 20°C: 150 ± centipoise (cP) at 23°C. Solid content: 89 ± 2 Flash point: > 61°C Drying times at 20°C - 50% RH</p> <ul style="list-style-type: none">• Polish ± 3-16 h• Maximum hardness: after 10 days• Can be used with care 1 day after polishing• Install furniture after 3 days• Lay carpets after 10 days• The surfaces can be cleaned with water or detergent after 1 month <p>Container size: 1L and 5L Shelf life: Maximum 2 years in its original container</p>
Surface preparation	OLÉOFLOOR® TRADITION should be applied to dry, clean, sound surfaces prepared according to the regulations in force. If necessary, depending on the type of wood, sand the wood beforehand with 100 to 120 grit.
Application tools	Short pile mohair roller, brush, cloth, rubber spatula or SPO/06E beige pad.
Recommandation before application	Large surfaces must be divided up into 20 to 50 m ² surfaces that can be treated in a period of 20 minutes. These should be reduced in the case of high temperatures or dry climates.
Dilutions	Ready to use, do not dilute.
Application	<ul style="list-style-type: none">• Apply OLÉOFLOOR® TRADITION generously and evenly in the direction of and across the grain, leave for 20 minutes and then rub with an impregnated beige pad, then remove any excess.• After 20 minutes, rub with a beige pad until the wood is saturated to spread the OLÉOFLOOR® TRADITION evenly. Add a bit more if necessary.• After 3 to 16 hours, perform a final polish with a FP/406W white pad or a BNN/406 active fibre pad.

Maintenance	For normal maintenance, use a damp floorcloth with a SOAPCLEAN* solution. Heavily used areas should be retreated with OLÉOFLOOR® TRADITION diluted 50% with white spirit (1 dose of OLÉOFLOOR® TRADITION / 1 dose of White-Spirit).
Coverage	15-20 m²/L depending on the type of wood.
Clean-up	White-Spirit. Pads and cloths soaked in oil can spontaneously catch fire. In order to avoid accidents, keep them outdoors in a closed, waterproof, metal container.
Storage	Keep away from freezing or high temperatures.
Safety	Refer to the safety data sheet (MSDS) available at www.owatrol.com and text on the packaging. Keep out of the reach of children.
Issue date	August 2016

* Same manufacturer

The information set out cons are purely illustrative and are not the responsibility of the manufacturer, the application of products not made under his supervision.

OWATROL INTERNATIONAL SLU
Barcelona – Spain
Tel. +34 93 125 88 68
Fax +34 93 106 02 13



Find all our solutions:
www.owatrol.com