



OWASAIL

SAIL RUST REMOVER

Description	OWASAIL is a cleaner for removing rust, mould and algae staining from sails and other fabrics. OWASAIL will also remove limescale and clean mould and algae staining from gelcoats.
Properties	<ul style="list-style-type: none">• Removes rust stain due to rusting deck equipment.• Dissolves and removes the build-up of limescale.• Cleans mould and algae stained surfaces.• Will not damage the surface.• Will not damage paintwork, varnish or woodstains in good condition.• Rinses with water.
Basic uses	<ul style="list-style-type: none">• Exterior• Sails, Boat covers, Fabrics....• Polyester, Dirty and algae affected gelcoats.
Technical data	<p>Solvent type: Water Specific Gravity at 20°C (68°F): 1.07 ± 0.05 Viscosity: Gel Solid content: 19% ± 2 Flash point: Not classified as flammable. Container size: 1L Shelf life: 18 months minimum in original unopened packaging. VOC: N/A under EU Directive 2004/42.</p>
Application tools	Brush. Roller. Sponge. Stiff synthetic scrubbing brush.
Good application practice	Cover everything you do not wish to treat. Do not apply in direct sunlight or to hot surfaces. Apply between 10°C (50°F) and 30°C (86°F). If in prolonged contact OWASAIL can tarnish metal surfaces. Use appropriate protective clothing – Gloves, Goggles.... Always test on a small inconspicuous area first.
Dilutions	Use as is. Do not dilute.
Application	Shake well before use. Wet surface with fresh clean water. Apply OWASAIL with brush or roller (Long Pile) Scrub surface, paying particular attention to the dirtiest areas. Allow to work 15-20 minutes. Rinse with plenty of fresh clean water while scrubbing. Repeat procedure if required.
Restrictions	Do not use on aluminium.
Clean-up	Water.
Storage	Store in original container. Close lid tightly after use. Keep from freezing and high temperatures.
General information	Every care is taken to ensure that the information provided in this technical data sheet is accurate. Owatrol International is unable to guarantee results as we have no control over the conditions under which our products are applied. For further advice and information please contact our technical department by email at info@owatrol.com or the local Owatrol Agent for your country. The information above is correct at the date of issue. All other OWATROL products named in this document should be used as per label instructions and the technical data sheet.
Safety	Refer to the safety data sheet (MSDS) available at www.owatrol.com and text on the packaging. Keep out of the reach of children.
Issue date	January 2017

* Same manufacturer

OWATROL INTERNATIONAL SLU
Barcelona – Spain
Tel. +34 93 125 88 68
Fax +34 93 106 02 13

OWASAIL
is a trademark



Find all our solutions:
www.owatrol.com